Geoenergetics in Poland

Tomasz Śliwa
Aneta Sapińska-Śliwa
19 Oct 2015

Definitions

- Geothermal
- Geothermal energy
- Geothermics
- Geoenergetics
- UTES
- BTES



Kępińska B., 2015



Geoenergetics Laboratory AGH UST

- AGH University of Science and Technology in Krakow
- Drilling, Oil and Gas Faculty
- Drilling and Geoengineering Department
- Geoenergetics Laboratory



BHEs



UTES BTES



First TRT in Poland 2007

OSSA Hotel 2007

- 612 kW_{th} 504 kW_{co} 80 BHEs





Geoenergetics Laboratory AGH UST

The Laboratory of Geoenergetics is equipped with 17 survey stands:

1. heating-cooling system of the FDOG Auditory,
2. apparatus for thermal response test (TRT),
3. heat pumps with bi-directional heat flow in the rock mass (heating and cooling),
4. borehole heat exchangers of various designs, each 78 m deep,
5. laboratory model of coaxial heat exchanger,
6. apparatus for measuring thermal power (teaching),
7. λ-meter for measuring thermal conductivity of rocks and materials (hardened sealing slurries, grouts),
8. apparatus NIMO-T for temperature logging in borehole heat exchangers,
9. meteo mini-station for measuring external temperature, speed and direction of wind and intensity of solar radiation,
10. five solar collectors for regeneration of heat in the rock mass with individual measurement,
11. heating/cooling system for snow melting of the parking before the Laboratory,
12. pressure meter for measuring location of the water table in the borehole,

Geoenergetics Laboratory AGH UST

and computer stands for calculations:

13. numerical simulator **BoHEx** for predicting exploitation in borehole heat exchangers in heating, cooling and heating/cooling systems,
14. RETScreen® International package for technical and economic analyses of renewable energy sources and determining their environmental impact,
15. **TOUGH2.o** numerical simulator for modelling exploitation in geothermal reservoirs with **PetraSim** pre- and postprocessor package,
16. BIES (Buildings' Integrated Evaluation System) computer program for analyzing the environmental impact of buildings,
17. AUDYTOR OZC program for determining buildings' heat demand.

Numerical modelling



Numerical modelling




W-E Horizontal distance from bondary of analyzed space, m
N-S Horizontal distance from bondary of analyzed space, m
Temperature, °C
Direction of water filtration in the interval 3-15 meters below the surface
BHE-1
BHE-2
BHE-3
BHE-4
BHE-5
Geoenergetics Laboratory Building

Testing ground in Pałecznica

Budynek	Moc grzewcza, kW	Liczba otworów	Sumaryczna głębokość wierceń, m	Moc jednostkowa, kW/m	Wymagana głębokość dla jednostkowej mocy, m/kW
1	2	3	4	5	6
A	44,4	20	600	74,00	13,51
B	29,3	12	360	81,39	12,29
C	11,1	5	150	74,00	13,51
Razem	86,8	37	1110	78,20	**12,78**

Direct evaporation BHEs



Testing ground in Pałecznica



Deep BHEs



Heat carrier circulation in deep BHE

Geoenergetics in Poland

Thank you

Tomasz Śliwa
Aneta Sapińska-Śliwa
19 Oct 2015